

Loopback Is A Virtual Network

S.MOHAN, Dr T.KALAIKUMARAN, R.SUGANYA

ASST PROFESSOR IN COMPUTER SCIENCE AND ENGINEERING

ASST PROFESSOR IN DEPARTMENT OF MATHAMETICS

V.S.B.COLLEGE OF ENGINEERING TECHNICAL CAMPUS

KINATHUKADAVU-COIMBATORE-642109.

TAMIL NADU. INDIA,.

Abstract:

In this paper we will discuss about virtual network or internal network. Because all network are inter connected between the devices and via through the network. Which is share the information and files are help with the common protocol (TCP/IP). But in the virtual network are also used with common protocol stack of (TCP/IP).this is internally build the address of IPv4 127.0.0.1 in IPv6 ::1. This address are does not visible on the system but it will do the process are internal or virtual . the connection with the help of IP address are itself. Every network are have the physical path . that is cable or wireless communication with the inter connected node (devices) are connected via through the networks . that will be share the information and files between the devices of the printer or any other computer peripherals of system, but the virtual or internal network create a path itself to transfer the data or files from the device internally this is external or physical network are not affected . so loopback is one of the virtual or internal networks. the loopback is never leaved nodes .so it is called virtual network.

Keywords: host, ip, tcp, ipv4, ipv6.

Introduction:

Already we are seeing the network. Because the network means either physical connection or wireless connection from one device to destination device .that is the address of (TCP/IP). The IP address is the information transfer to the device to device with the common protocol. The protocol means some set of rules to fix and transfer the data or information .it is called external network or physical network . in internal or virtual network are used to transfer he information from the device itself. Because router and switches are already build in the system. that ip address are 127.0.0.1. it is a software based networks . That creates logical isolation and communication between the devices such as a virtual machine. Without being tied to physical hardware. This is use of the software mimic a physical network. it is allowing to flexibility cost saving and scalability by create multiple isolation network on a single physical infrastructure .the virtual network (the overlay)runs on the top of the physical network .the (under lay) which is provide the basic connectivity.

Local host:

The local host refer the current computer are using ,allowing a program to connect the network services an itself, rather than the remote server. It is use the loopback network interfaces, which send the data itself and its commonly associated with IP address(127.0.0.1). this is most offer used by develop testing and developing application locally without needed by the physical network or internet connection.

Which are type of “local host” in to a web browser. It act as a host name the computer recognized and referring to itself .which is solve the loopback IP address 127.0.0.1 for IPv4.

This is send data to the computer own network interface, bypassing any external network hardware . simulated server by using the local host your computer can act as both the client and server allowing you to run and test the application locally as they were as a live server. It is used to access services that are running an your own computer like local web server or database.

Server:

Local host is a server specifically a server that is running on your own computer it is used for local connection allowing you to access and test application or web site on your machines without connection to the internet.

Virtual server


When you are access to the local host your computer is acting as a virtual server communicating with itself through the special IP address most commonly the loopback address 127.0.0.1.

Indeed for development:

This is especially useful for development of want to build and test the application in closed environment before deployment them publically.

Self- contained test

By using local host you test the full functionality of a program or web site directly on the machine. Where it is developed which is truth and more efficient then using the remote server.



Loopback interface:

It is commonly represented with a client-server or web application such a diagram a local host refer to the used own machine and is used for local development and testing it is multi tier application run on the server physical computer.

Communication each other via a virtual network interface it can be assigned and IP address that review the contrast ,making it is reliable identifier for the device which useful for management tool.

The packet send to the loopback address are handled internally making it idea for testing network software and connecting without needing physical network connection.

Internal traffic send to the loopback address is routed to the device itself rather the being transmitted and on the physical networks, the loopback interface simulated network connection with in the single machine without ever involving external network or hardware which fundamentally different from how the internet operate.

The loopback is a logical interface not physical network. It is a virtual interface on a device (the router and the computer). That allow to device to send and receive data to and from itself offer used for testing and management purpose .the loopback interface is always up and stable and it uses reserved address range (127.0.0.1) to identify the device itself even if all physical network connection fail.

Benefit of loopback:

Loopback interfaces are excellent for network diagnosis and troubleshooting ex. PING. On the loopback address to verify that the IP address to verify that IOP stack functioning currently identify of the physical hardware . it will give the protocol and fire wall rules without affecting live network operations

Loopback is a virtual network:

Loopback inter faces are virtual network interfaces implied entirely in software it is not tied to any physical hardware and function as on internal communication channel with in a single device.

Internal communication

Traffic sent to the loopback address is immediately routed back by some machine network software stack without ever leaving the computer or involving in external network or hardware.

Reserved address

The IPv4 address range reserved for loopback is 127.0.0.1to 127.255.255.255 (127.0.0.1/8 block)with 127.0.0.1 (the host name local host being the most commonly used address . the IPv6 loopback address is ::1.

Always active

The loopback interface is a stack always-up interface as it to availability is independent of the status any physical network connection.

Destination from a virtual networks

While loopback interface is a type of virtual interface it is not a “virtual network” in the broad sense of the term .a virtual network typically implies configuration that connect multiple virtual machines or systems.

Over a simulated network environment often using the technology like VPN(virtual private networks). Virtual with a hypervisor .the loopback interface , by contrast, is a self contained mechanism for a single machine to talk itself.

Conclusion:

The loopback is a virtual networks is not actually network .because it is interfaces from and to in a single machine itself. If not activated in a physical network the loopback is transfer the data or information itself. So it is called virtual network of the system. it has stable in the system. While physical network failure the data will be transfer from the node without affecting the physical networks never leaved to the node . it is self contained mechanism for the single machine to transfer data or information itself. So it is called interfaces of the internal network .it has fixed IPv4address (127.0.0.1) in IPv6(::1). T is not visible but it help to transfer the data itself to the system . it is best for ping. To tied the trouble shooting (RTT) running trip time for the ping process in virtual network. It is not a browser. The loopback is a interface-internally .so it is called virtual network.

References:

1. Jaya Suseela and Venkatesan Muthukumar "Loopback Virtual Channel Router Architecture for Network on Chip" 2012 Ninth International Conference on Information Technology-New Generations.
2. Amit Kumar Lamba, Bharati B. Sayankar "Performance Analyses of Speculative Virtual channel router for Network-On-Chip"2013.
3. Mostafa S. Sayed, A. Shalaby, M. El-Sayed Ragab, Victor Goulart "Congestion Mitigation Using Flexible Router Architecture for NoC" IEEE 2012 Japan-Egypt Conference on Electronics, Communications and Computers.
4. Son Truong Nguyen, Shigeru Oyanagi "The Design of On-the-fly Virtual Channel Allocation for Low Cost High Performance On-Chip Routers" IEEE 2010 First International Conference on Networking and Computing.
5. Feiyang Liu, Huaxi Gu, Yintang Yang "Performance Study of Virtual-Channel Router for Network-on-Chip" IEEE 2010 International Conference On Computer Design And Appliations (ICDDA 2010).
6. R. Mullins, A. West and S. Moore, "Low-Latency Virtual-Channel Routers for On-Chip Networks", Proceedings of the31st Annual International Symposium on Computer Architecture, pp. 188-197, Jun. 2004.
7. R. Mullins, A. West and S. Moore, The Design and Implementation of a Low Latency On-Chip Network", Proceedings of the Asia and South Pacific Design Automation Conference (ASP-DAC-06), pp. 164-169, Jan. 2006.
8. D. Bertozzi and L. Benini, Xpipes: "A Network-on-Chip architecture for Gigascale Systems-on-Chip", IEEE Circuitsand Systems Magazine, pp. 18-31, Q. 2 2004.